


Stromkabel aus mehrdrähtigem Kupfer mit besonders flexibler PVC-Hülle.

Kann im Innen- und Außenbereich, in trockener oder feuchter Umgebung verwendet werden.



Art-Nr.	054882	054875	054905	054899	054929	054912	054943	054936	054967	054950	-	056565
Farbe	●	●	●	●	●	●	●	●	●	●	●	●
Querschnitt (mm ²)	10		16		25		35		50			70
Dicke der Isolierung (mm)	1.4		1.4		1.5		1.7		1.7			1.9
Ø Kabelquerschnitt (mm)	7.3		8.7		10.5		12.0		13.8			15.9
Adern	Anzahl	288	204		324		444		636			900
	Ø (mm)	0.2	0.3		0.3		0.3		0.3			0.3
Intensité admissible à 20°C (A)	mit Außenhülle	50	65		85		106		129			164
	ohne Außenhülle	57	73		97		121		145			184
Zulässige Stromstärke bei 20°C(Ω/km)	1.91		1.31		0.85		0.595		0.419			0.297
Gewicht (kg pour 100 m)	13		20		30		41		56,5			78
Markierung	HI-FLEX «size» MM ² CE											
Isoliermaterial	PVC											
Betriebstemperatur	Transportabel	+5°C / +70°C										
	Feststehend	-30°C / +70°C										
Nennspannung U ₀ / U	450 / 750V											
Krümmungsradius	Transportabel	4 x Ø du câble										
	Feststehend	3 x Ø du câble										
	100 m											50 m
Norme	IEC60332-1 / EN 60332-2-1:2004											