



## Stromkabel aus mehrdrähtigem Kupfer mit besonders flexibler PVC-Hülle.

Kann im Innen- und Außenbereich, in trockener oder feuchter Umgebung verwendet werden.



Art-Nr.	056107	056091	056121	056114	056145	056138	056169	056152	056183	056176
Farbe	●	●	●	●	●	●	●	●	●	●
Querschnitt (mm <sup>2</sup> )	10		16		25		35		50	
Dicke der Isolierung	1.4		1.4		1.5		1.7		1.7	
Ø Kabelquerschnitt (mm)	7.3		8.7		10.5		12.0		13.8	
Adern	Anzahl	288	204		324		444		636	
	Ø (mm)	0.2	0.3		0.3		0.3		0.3	
Zulässige Stromstärke bei 20°C	Hülle	50	65		85		106		129	
	Frei verlegbar	57	73		97		121		145	
Widerstand bei 20 °C (Ω/km)	1.91		1.31		0.85		0.595		0.419	
Gesamtgewicht (kg/km)	130		200		300		410		565	
Markierung	HI-FLEX «size» MM <sup>2</sup> CE MADE IN EC									
Isoliermaterial	PVC									
Betriebstemperatur	Transportabel	+5°C / +70°C								
	Feststehend	-30°C / +70°C								
Nennspannung U <sub>0</sub> / U	450 / 750V									
Krümmungsradius	Transportabel	4 x Ø du câble								
	Feststehend	3 x Ø du câble								
	20m									
Norme	IEC60332-1 / CEI EN 50265								