



## Cable eléctrico de cobre multihilos con funda exterior en PVC

Se puede utilizar en el interior, el exterior y en ambiente seco o húmedo.



Ref.		056107	056091	056121	056114	056145	056138	056169	056152	056183	056176
Color		●	●	●	●	●	●	●	●	●	●
Sección (mm <sup>2</sup> )		10		16		25		35		50	
Grosor de aislamiento		1.4		1.4		1.5		1.7		1.7	
Ø del cable (mm)		7.3		8.7		10.5		12.0		13.8	
Hebras	Número	288		204		324		444		636	
	Ø (mm)	0.2		0.3		0.3		0.3		0.3	
Intensidad admisible a 20°C	En funda	50		65		85		106		129	
	Suelto	57		73		97		121		145	
Resistencia a 20 °C (Ω/km)		1.91		1.31		0.85		0.595		0.419	
Peso total (kg/km)		130		200		300		410		565	
Marcado		HI-FLEX «size» MM <sup>2</sup> CE MADE IN EC									
Material de aislamiento		PVC									
Temperatura de funcionamiento	móvil	+5°C / +70°C									
	fijo	-30°C / +70°C									
Tensión nominal U <sub>0</sub> / U		450 / 750V									
Radio de curvatura	móvil	4 x Ø del cable									
	fijo	3 x Ø del cable									
		20m									
Norma		IEC60332-1 / CEI EN 50265									
		