

WS-4L zasebni dodavač žice s vodenim hlađenjem kompatibilan je s MAGYS 500 WS. Stroj za zavarivanje.

SINERGIJSKI


- **Sinergijska funkcija:** Postavka brzine žice kontrolira se iz dodavača žice.

INDUSTRIJSKI

- Može se opremiti vodenom hlađenim plamenicima za optimalnu produktivnost.
- Njegova teška konstrukcija osigurava dug radni vijek.
- Njegov sustav pogona na 4 kotača u kombinaciji s motorom od 75 W osigurava učinkovito uvlačenje žice bilo koje vrste.

MOBILNI

- Isporučuje se s nosačem dodavača žice za pričvršćivanje na generator za zavarivanje. Dodavač žice može se postaviti na nosač dodavača žice ili se može pomicati po tlu s dodatnim kolicima za dodavač žice.
- Vodeno hlađeni međuspojni kabeli od 1,6 m do 20 m.
- Podizanje očiju.




WS-4L dodavač žice
ref. 033573

Pogledajte tehnički list:
MAGYS 500 WS - ref. 032200

VRSTA PAKIRANJA : ref. 032330 (bez regulatora)

				
MAGYS 500 WS ref. 032200	WS-4L dodavač žice ref. 033573	Međuspojni kablovi 10m - 70 mm ² ref. 033658	Kabel za uzemljenje 4m - Ø 70 mm ² ref. 043831	Čelik / nehrđajući čelik 500A - 4m (VODA) ref. 041004

OPCIJE

Kolica za WS dodavač žice
040977




Regulator 30L/min
 041622
 041219
  041646



Kabel za promjenu polariteta
033689

Međuspojni kablovi

L.	VODA	
	Ø	Ref.
1,6m	70 mm ²	033696
5m	70 mm ²	033641
10m	70 mm ²	033658
10m	95 mm ²	034877
15m	95 mm ²	034884
20m	95 mm ²	034891

≡		⊕ ⊖ ∅m		⊕ ⊖ ∅m		⊕	équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica	EN60974-5 (40 °C)	IP	↕ / ⚠
U ₁	I ₁	GAS	NO GAS	200	300	Electronic Control	⊕			cm/kg
24V	4A	0,6 - 1.6	0,9 - 2.4	✓	✓	 75W	1.0 - 1.2	410A @ 60 % 320A @ 100 %	23S	25x59x56 / 17