


Elektrische kabel van koperdraad met extra soepele kabelhuls van PVC.

Kan binnen en buiten gebruikt worden, in droge of vochtige omgevingen.



Ref.	054882	054875	054905	054899	054929	054912	054943	054936	054967	054950	-	056565
Kleur	●	●	●	●	●	●	●	●	●	●	●	●
Sectie (mm ²)	10		16		25		35		50			70
Dikte van het isolatiemateriaal	1.4		1.4		1.5		1.7		1.7			1.9
Ø van de kabel (mm)	7.3		8.7		10.5		12.0		13.8			15.9
Bundels	Aantal	288	204		324		444		636			900
	Ø (mm)	0.2	0.3		0.3		0.3		0.3			0.3
Toegestane stroomsterkte bij 20°C	In kabelhuls	50	65		85		106		129			164
	Losliggend	57	73		97		121		145			184
Weerstand bij 20°C (Ω/km)	1.91		1.31		0.85		0.595		0.419			0.297
Totaal gewicht (kg/km)	130		200		300		410		565			780
Markering	HI-FLEX «size» MM ² CE MADE IN EC											
Isolatie materiaal	PVC											
Gebruiks temperatuur	mobiel	+5°C / +70°C										
	vast	-30°C / +70°C										
Nominale spanning U ₀ / U	450 / 750V											
Kromtestraal	mobiel	4 x Ø van de kabel										
	vast	3 x Ø van de kabel										
	100m											
Norm	IEC60332-1 / CEI EN 50265										