



Elektrische kabel van koperdraad met extra soepele kabelhuls van PVC.

Kan binnen en buiten gebruikt worden, in droge of vochtige omgevingen.



Ref.		056107	056091	056121	056114	056145	056138	056169	056152	056183	056176	
Kleur		●	●	●	●	●	●	●	●	●	●	
Sectie (mm ²)		10		16		25		35		50		
Dikte van het isolatiemateriaal		1.4		1.4		1.5		1.7		1.7		
Ø van de kabel (mm)		7.3		8.7		10.5		12.0		13.8		
Bundels	Aantal	288		204		324		444		636		
	Ø (mm)	0.2		0.3		0.3		0.3		0.3		
Toegestane stroomsterkte bij 20°C	In kabelhuls	50		65		85		106		129		
	Losliggend	57		73		97		121		145		
Weerstand bij 20°C (Ω/km)		1.91		1.31		0.85		0.595		0.419		
Totaal gewicht (kg/km)		130		200		300		410		565		
Markering		HI-FLEX «size» MM ² CE MADE IN EC										
Isolatie materiaal		PVC										
Gebruiks-temperatuur	mobiel	+5°C / +70°C										
	vast	-30°C / +70°C										
Nominale spanning U ₀ / U		450 / 750V										
Kromtestraal	mobiel	4 x Ø van de kabel										
	vast	3 x Ø van de kabel										
		20m										
Norm		IEC60332-1 / CEI EN 50265								