

The EASYMIG 130 is a semi-automatic machine that combines MIG/MAG, cored wire and MMA welding processes. Thanks to its user-friendly interface, the voltage and wire speed settings are made easier. Ultra-light, it is easy to carry around. The EASYMIG 130 is recommended for welding steel, stainless steel and occasionally aluminium.

3 in 1

- MIG-MAG GAS
- MIG-MAG NO GAS
- MMA



Ultra-light and portable

- 8.6 kg weight .
- Ergonomic handle.

Easy set up



- Voltage set selection from 15 to 20 V.
- Wire speed selection from 3 to 9 m/min.

Sturdy build quality

- Reinforced mechanical structure.
- Pads for shock and vibration absorption.

Integrated wire feeder

- ø100 (1 kg) wire reels.
- 2 rollers motor
- Supplied rollers :
 - steel : 0,8
 - no gas : 0,9

Connected MAG torch

- Fixed torch 120 A - 2.20 m fitted for steel.

Simplified display



- 2 colour LED to display :
- Thermal protection.
 - Power up.

MIG/MAG - MMA

- Wire diameter Ø 0,6 mm to 0,8 mm.
- Electrode Ø 1,6 mm to 3,2 mm.

Polarity reversal cable

- For NO GAS welding.

Features



Inverter technology to ensure an excellent welding current quality and a low electric consumption



Can weld rutile electrodes . Antisticking (prevents electrode sticking at start).



Can weld :
- MIG/MAG wire with gas
- MIG/MAG cored wire without gas

NO GAS ready to weld

This process allows :

- Welding with cored wire (requires polarity reversal).
- Allows outdoor welding (not wind. affected...)
- Increased portability due to absence of gas bottles.
- Ideal for outdoors work on thin metal sheets.

Includes

- **Earth clamp**
(cable 1.6 m / 16 mm²)
- **Electrode holder**
(cable 1.6 m / 10 mm²)
- **Accessories bag**
 - Contact tip 0.9 mm.
 - Gas nozzle (gas).
 - Tightening key for contact tips.
 - Gas tube 1 m.
 - 2 clamps for the gas tube.



50/60hz	MMA I ²	min▷max	ømm		100	Electronic Control	équipé d'origine / original equipment / originalausstattung / equipamiento de fabrica		EN60974-1 (40°C)				cm/kg
			GAS	NO GAS			MIG	MMA	I _A (60%)	X% (I ₂ max)	I _A (60%)	X% (I ₂ max)	
230V 1~	16A	20▷100A	30▷120A	0.6 - 0.8	0.9	✓	0.8 - 0.9	0.8	70A	120A 20%	60A	100A 20%	38x16x35 / 8,6