

3 Phase MMA – TIG Lift 250A – 400V Capable of functioning on a long power cable Works on a wide range of input voltage (340V > 460V).

For unbeatable price and performance, the 250 A TRI is ideal for MMA (Electrode) welding on a 3 phase network. With a protection rating of IP21, the machine is very robust. The machine features a touch key-pad and digital display. Its duty cycle is suitable for professional work in mechanised welding, sheet metal and piping.

MMA (250A)

- ✓ The 250 A Tri's flexible arc dynamic allows it to weld Steel, Stainless Steel, Cast Iron, Rutile or Basic electrodes easily.
- ✓ In addition to **Anti-sticking**, this product features:
 - Adjustable **Hot-Start** : facilitates the ignition of all types of metal
 - Low Hot start for thin metals
 - High Hot start for difficult to weld metals (dirty or oxidised pieces)
 - Adjustable **Arc force** : for better penetration and prevention of sticking.



Without accessories

TIG Lift (250A)

- ✓ Easy start with TIG-Lift feature:
Machine prevents tungsten inclusions and radio electrical disturbances.
- ✓ To ensure a smooth welding bead, the PROGYS 250 A Tri includes an innovative « Arc Down Slope » function with:
 - Automatic release - with a simple movement with the torch
 - Adjustable down-slope

OPTIONAL (ref 047341)
MMA Kit
- Length: 4 m
- Connector 35 mm²







PROFESSIONAL UNIT

IP21

Equipped with an IP21 protection rating, it is protected against access to dangerous parts with a finger, and against vertical drops of water drops.

PROGYS 250 A TRI is particularly suitable for outdoor work on site

50/60hz	AM	I ₂								EN60974-1 (40°C)		U ₀				
		TIG	MMA	Ø 1.6	Ø 2	Ø 2.5	Ø 3.2	Ø 4	Ø 5	I _A (60%)	X% (I ₂ max)					
400V 3~	16A	5-250 A		62	50	47	45	38	19	120A	15%	66V	35/50	cm/kg	20x42x32 / 11.3	10 kW 12.5 kVA