

Its integrated technology enables a steady weld. Ideal for beginners. It's also a light machine (2.5kg) easy to carry.

ELECTRODES FROM 1.6 TO 2.5

- Welds Rutils, Cast-iron and Stainless-steel electrodes
- At 20°C, it welds 1 electrode Ø2.5 every 2 minutes


ARC QUALITY

- Instantaneous start
- High penetration and arc stability



POWER CONTROLLED

- Low consumption 10A-230V
- Tolerant to current fluctuation or arc length
- Protected and compatible with generator 3Kw (3.75Kva)



INVERTER TECHNOLOGY


HOT START
Additional power to start the arc



ANTISTICKING
Decrease of current to release the electrode



ARC FORCE
Instantaneous increase of current



FEATURES

Delivered with :

- Earth clamp
- Electrode holder
- Strap

Also available in a plastic case with:

- Earth clamp
- Electrode holder
- Strap
- Chipping hammer and brush
- Hand mask



Ref: 015579



CE - EN 60974-1

50/60Hz	+AM+	I ₂ MMA (A)	1h	MINI 20°					X% (20°C)	EN60974-1 (40°C)		U ₀	Cm	Kg	Protected & compatible Power generator (+/- 15%)
				Ø1,6	Ø2	Ø2,5	Ø3,2	Ø4		IA (60%)	X% (12 max)				
230V	10A	10 → 80	62	50	20	-	-	45%@80A	31A	6%	85V	10x14x23	2.5	3 Kw - 3.7 Kva	