



Professional battery tester providing highly accurate measurements.

## FEATURES

- **Battery 12 V:** test of the voltage and state of charge.
- **Starter 12 & 24 V:** test of the start voltage.
- **12 & 24 V Alternator:** tests no load voltage and charging voltage as well as current undulation during the charge.

## INSTANT ANALYSIS

- Battery voltage (8 V to 30 V)
- Available starting power
- Charge state and battery health (%)

## BATTERY TYPES

- Compatible with **3 types of lead-acid battery** ranging from **7 to 240 Ah**:
  - VRLA / GEL / AGM FLAT / AGM SPIRAL sealed batteries
  - STANDARD LIQUID batteries
  - START / STOP batteries (EFB/AGM)
- **Operating ranges :**
  - 🇪🇺 EN : 40 > 1885 CCA
  - 🇩🇪 DIN : 25 > 1120 CCA
  - 🇺🇸 SAE/CCA : 40 > 2000 CCA
  - 🇯🇵 JIS : japanese battery
  - 🌐 IEC : 30 > 1320 CCA (international standard)
  - CA/MCA : 50 > 2400 CCA (marine battery)



## HIGHLY ACCURATE

- Automatic compensation of external temperature.
- The dynamic resistance measuring technology minimises battery discharge and displays a reliable result unaffected by:
  - surface charge
  - vehicle consumers (lights, various indicators, etc)
  - contact defaults (worn out terminals/ lugs, unfastened lugs, etc)

## PRACTICAL

- Insulated clamps
- Large backlit «4-line» display for better viewing
- Adjustable screen brightness
- Retroactive «ENTER» key
- Multilingual interface (10 languages)
- Reverse polarity protection
- ABS housing (acid-proof) + shock protection

		TEST				RESULT		TEMPERATURE COMPENSATION	cm	
Battery		Battery A	Battery V	CHARGING & STARTING SYSTEM VEHICLE						
12 V	7 >240 Ah	•	• min 8 V	12 V 24 V	1 s	instant	•	13,8 x 9,6 x 3	40 cm	